


#### HS2SR10SP830NW



## HANCE G2 SEMIREC 1000 WW SP WH

#### **Description:**

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 1000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 3000K y CRI80. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

#### Installation: Semi-Recessed

### **TECHNICAL SPECIFICATIONS:**

Light output:	995 lm	<b>°K</b> :	3000	
Plum:	8,6W	CRI :	80	
Efficacy:	115,7 lm/w	R9 :	60	
UGR:	<16	MacAdam:	3	
Туре:	СОВ	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	78.000 L80B10 (Ta=25°C)	Gear:	Electronic	
Power:	7W			

### Light output tolerance +/- 10%



## **CUSTOM MADE OPTIONS:**





HS2SR10SP830NW

HANCE G2 SEMIREC 1000 WW SP WH

## PHOTOMETRIC DATA :

HS2SR10SP830NW	180°	alpha = 19,6°	100%	BACK	FRONT
η = 100%		$\land$	75%	50,0 %	50,0 %
Imax = 4956 cd/klm		/ \	50%	50,0 70	
UTE:	90° 90°				V I
CIE: 102 100 100 100 100			25%		
	0.			-8H -4H	0H 4H 8H

# ACCESORIES :

## Optical



Product code: HSCU50





Product code: HSHO50

Description: HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description: HANCE 1000/2000 ACC. RING DECO CO.



Product code: HSRI65M

Description: HANCE 1000/2000 ACC. RING DECO MET.



Product code: HSRI65W





Product code: HSSL50

Description: HANCE 1000/2000 ACC. SOFT LENS



Product code: HSTR50

Description: HANCE 1000/2000 ACC. DIF TRANS