


HS2SR10SP840DB



HANCE G2 SEMIREC 1000 NW SP DALI BK

Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 1000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.054 lm	°K :	4000	
Plum:	8,6W	CRI :	80	
Efficacy:	122,6 lm/w	R9 :	66	
UGR:	<16	MacAdam:	3	
Туре:	СОВ	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	78.000 L80B10 (Ta=25°C)	Gear:	Adjustable DALI	
Power:	7W			

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:





HS2SR10SP840DB

HANCE G2 SEMIREC 1000 NW SP DALI BK

PHOTOMETRIC DATA :

HS2SR10SP840DB	180°	alpha = 19,6°	100%	BACK	FRONT
η = 100%		\land	75%	50,0 %	50,0 %
lmax = 4956 cd/klm			50%		
UTE:	90° 90°				- M
CIE: 102 100 100 100 100			25%		
	0 °			-8H -4H	0H 4H 8H

ACCESORIES :

Optical



Product code: HSCU50





Product code: HSHO50

Description: HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description: HANCE 1000/2000 ACC. RING DECO CO.



Product code: HSRI65M

Description: HANCE 1000/2000 ACC. RING DECO MET.



Product code: HSRI65W





Product code: HSSL50

Description: HANCE 1000/2000 ACC. SOFT LENS



Product code: HSTR50

Description: HANCE 1000/2000 ACC. DIF TRANS