


HS2SR20SP840NW



HANCE G2 SEMIREC 2000 NW SP WH

Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 2000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 4000K y CRI80. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Semi-Recessed

TECHNICAL SPECIFICATIONS:

Light output:	2.335 lm	٩ κ :	4000	
Plum:	20,8W	CRI :	80	
Efficacy:	112,3 lm/w	R9 :	66	
UGR:	<19	MacAdam:	3	
Туре:	СОВ	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	72.000 L80B10 (Ta=25°C)	Gear:	Electronic	
Power:	18W			

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:





HS2SR20SP840NW

HANCE G2 SEMIREC 2000 NW SP WH

PHOTOMETRIC DATA :

HS2SR20SP840NW	180°	alpha = 19,6°	100%	BACK	FRONT
η = 100% Imax = 4956 cd/klm			75%	50,0 %	50,0 %
UTE:	90° 90°		50%		
CIE: 102 100 100 100 100			25%		
				-8H -4H	0H 4H 8H
	00				

ACCESORIES :

Optical



Product code: HSCU50





Product code: HSHO50

Description: HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C

Description: HANCE 1000/2000 ACC. RING DECO CO.



Product code: HSRI65M

Description: HANCE 1000/2000 ACC. RING DECO MET.



Product code: HSRI65W





Product code: HSSL50

Description: HANCE 1000/2000 ACC. SOFT LENS



Product code: HSTR50

Description: HANCE 1000/2000 ACC. DIF TRANS