


HS2SR30MF840NB



HANCE G2 SEMIREC 3000 NW MFL BK

Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 3000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K y CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.549 lm °K: 4000 Plum: 28,3W CRI: 80 Efficacy: 125,4 lm/w R9: 64 UGR: <19 MacAdam: 3

Type: COB **Power Supply**: 220-240V 50/60Hz

LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Electronic

Power: 25W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















HS2SR30MF840NB


HANCE G2 SEMIREC 3000 NW MFL BK

PHOTOMETRIC DATA:

HS2SR30MF840NB η = 100% Imax = 3926 cd/klm UTE: CIE: 101 100 100 100 100









ACCESORIES:

Optical



Product code:

HS2HO75



Product code:

HANCE G2 3000/4000 ACC. HONEYCOMB GRILLE HS2RI90C



HANCE G2 3000/4000 ACC. RING DECO CO.



Product code:

HS2RI90M



Product code:

HS2RI90W

Description:

HANCE G2 3000/4000 ACC. RING DECO WH.



Product code:

HS2TR75



Description:

Description:

HANCE G2 3000/4000 ACC. DIF TRANS

HANCE G2 3000/4000 ACC. RING DECO MET.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS