


#### HS2SR30SP840DB



## HANCE G2 SEMIREC 3000 NW SP DALI BK

#### Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 3000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output: 3.419 lm °K: 4000 Plum: 28,3W CRI: 80 Efficacy: 120,8 lm/w R9: 64 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Adjustable DALI

25W Power:

#### Light output tolerance +/- 10%

































# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU



















## HS2SR30SP840DB


## HANCE G2 SEMIREC 3000 NW SP DALI BK

#### **PHOTOMETRIC DATA:**

HS2SR30SP840DB η = 100% Imax = 5192 cd/klm UTE: CIE: 102 100 100 100 100









## ACCESORIES:

## Optical



Product code:

HS2HO75



Product code:

HANCE G2 3000/4000 ACC. HONEYCOMB GRILLE HS2RI90C



HANCE G2 3000/4000 ACC. RING DECO CO.



Product code:

HS2RI90M



Product code:

HS2RI90W

Description:

HANCE G2 3000/4000 ACC. RING DECO WH.



Product code:

HS2TR75



Description:

Description:

HANCE G2 3000/4000 ACC. DIF TRANS

HANCE G2 3000/4000 ACC. RING DECO MET.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS