


HS2SR40SP840NW



HANCE G2 SEMIREC 4000 NW SP WH

Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 4000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 4000K y CRI80. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Semi-Recessed

TECHNICAL SPECIFICATIONS:

Light output:	4.694 lm	⁰К:	4000		
Plum:	36,7W	CRI :	80		
Efficacy:	127,9 lm/w	R9 :	64		
UGR:	<19	MacAdam:	3		
Туре:	СОВ	Power Supply:	220-240V 50/60Hz		
LED Lifetime:	72.000 L80B10 (Ta=25ºC)	Gear:	Electronic		
Power:	33W				

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:





HS2SR40SP840NW

HANCE G2 SEMIREC 4000 NW SP WH

PHOTOMETRIC DATA :

HS2SR40SP840NW	180°	alpha = 19,6°	100%	BACK	FRONT
η = 100%		\land	75%	49,9 %	49,9 %
Imax = 5192 cd/klm		/ \	50%		
UTE:	90° 90°				
CIE: 102 100 100 100 100			25%		
	0°			-8H -4H	0H 4H 8H



ACCESORIES :

Optical



Product code: HSSL50 Description: HANCE 1000/2000 ACC. SOFT LENS