KOMBIC 100 DOWNLIGHT




K11RD1523RW927DWW

KOM 100 RD 1500 IP23 9VWW RF WFL DA WH/W



Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic DALI wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Shiny white RAL 9010

Weight: 382 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.264 lm °K: 2700 Plum: 14,2W CRI: 90 Efficacy: 88,9 lm/w R9: 58 Type: СОВ MacAdam: 3

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz Gear: Power: 13W Adjustable DALI

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU











KOMBIC 100 DOWNLIGHT



K11RD1523RW927DWW

KOM 100 RD 1500 IP23 9VWW RF WFL DA WH/W

PHOTOMETRIC DATA:

K11RD1523RW927DWW $\eta = 100\%$

Imax = 1215 cd/klm

UTE: 1,00A

CIE: 94 97 99 100 100

