KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11RD1523RW927NBB — **KOMBIC 100 RD 1500 IP23 9VWW RF WFL B/B**

Description:

```
25
75
ø99
```

Finish: Matte black RAL 9011

Weight: 382 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.168 lm	**ºK :**	2700
Plum:	14,5W	**CRI :**	90
Efficacy:	80,5 lm/w	**R9 :**	58
UGR:	<19	**MacAdam:**	3
Type:	COB	**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	**Gear:**	Electronic
Power:	13W		

Light output tolerance +/- 10%

EPD

Tel. +34937366800

Web www.lamp.es

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU

15-05-2025

Pág. 1 / 2

LAMP
Worktitude for light

K11RD1523RW927NBB   **KOMBIC 100 RD 1500 IP23 9VWW RF WFL B/B**

PHOTOMETRIC DATA :

K11RD1523RW927NBB

η = 100%

Imax = 1293 cd/klm

UTE:

CIE: 99 100 100 100 100

alpha = 59,5º

BACK   FRONT

49,9 %   49,9 %

Melanopic Lux Ratio: 0.504

Rf

1 - Limits on the Planckian locus

Rg

2 - Limits for practical sources

Rf 91.6 – Rg 99.6

15-05-2025

Pág.   2 / 2

Data according to regulations 2019/2020/EU and 2019/2015/EU