


## KOMBIC 100 DOWNLIGHT

K11RD1523RW940DWW



KOM 100 RD 1500 IP23 9NW RF WFL DA WH/WH

**Description:**

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution. . Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Shiny white RAL 9010**Weight:** 382 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.406 lm	<b>°K :</b>	4000
<b>Plum:</b>	14,2W	<b>CRI :</b>	90
<b>Efficacy:</b>	99 lm/w	<b>R9 :</b>	65
<b>Type:</b>	COB	<b>MacAdam:</b>	3
<b>LED Lifetime:</b>	50.000 L80 B10 (Ta=25°C)	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Power:</b>	13W	<b>Gear:</b>	Adjustable DALI

*Light output tolerance +/- 10%***CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD1523RW940DWW

KOM 100 RD 1500 IP23 9NW RF WFL DA WH/WH

PHOTOMETRIC DATA :

