


KOMBIC 100 DOWNLIGHT

K11RD1523RW940NBW



KOMBIC 100 RD 1500 IP23 9NW RF WFL BK/WH

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution and low glare level UGR 17. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011

Weight: 382 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.299 lm	°K :	4000
Plum:	14,5W	CRI :	90
Efficacy:	89,5 lm/w	R9 :	65
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	13W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RD1523RW940NBW

KOMBIC 100 RD 1500 IP23 9NW RF WFL BK/WH

PHOTOMETRIC DATA :

