


KOMBIC 100 DOWNLIGHT

K11RD1523RW940NMW



KOMBIC 100 RD 1500 IP23 9NW RF WFL MA/WH

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Weight: 382 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.406 lm	°K :	4000
Plum:	14,5W	CRI :	90
Efficacy:	96,9 lm/w	R9 :	65
Type:	COB	MacAdam:	3
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	13W	Gear:	Electronic

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



## KOMBIC 100 DOWNLIGHT

K11RD1523RW940NMW

KOMBIC 100 RD 1500 IP23 9NW RF WFL MA/WH

## PHOTOMETRIC DATA :

