# **KOMBIC 100 DOWNLIGHT**


## K11RD1540OP940DMW



## KOMBIC 100 RD 1500 IP43 9NW OP DA MA/WH

#### **Description:**

Round recessed downlight model KOMBIC 100 RD 1500 IP43 9NW OP DA MA/WH, LAMP brand. Reflector made of polycarbonate. Matte metallic interior reflector and frame in white finish, and optical film, die cast aluminium heat sink. Model for LED COB, with neutral white colour temperature and control DALI gear included. IP43 protection rating. Insulation class II. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: metalized polycarbonate mate


Weight: 425 g

Installation: Recessed

# **TECHNICAL SPECIFICATIONS:**

Light output:	1.273 lm	⁰K :	4000
Plum:	13,4W	CRI :	90
Efficacy:	95 lm	R9 :	66
Туре:	СОВ	MacAdam:	3
LED Lifetime:	50.000 L80 B10 (Ta=25⁰C)	Power Supply:	220-240V 50/60Hz
Power:	12W	Gear:	Adjustable DALI

## Light output tolerance +/- 10%



# **CUSTOM MADE OPTIONS:**



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light