


## KOMBIC 100 DOWNLIGHT

K11RD1540WF930DMW




## KOMBIC 100 RD 1500 IP43 9WW WFL DA MA/WH

**Description:**

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** metalized polycarbonate mate**Weight:** 442 g**Installation:** Semi-Recessed**TECHNICAL SPECIFICATIONS:**

<b>Plum:</b>	13,4W	<b>°K :</b>	3000
<b>UGR:</b>	<19	<b>CRI :</b>	90
<b>Type:</b>	COB	<b>R9 :</b>	62
<b>LED Lifetime:</b>	50.000 L80 B10 (Ta=25°C)	<b>MacAdam:</b>	3
<b>Power:</b>	12W	<b>Power Supply:</b>	220-240V 50/60Hz
		<b>Gear:</b>	Adjustable DALI

**CUSTOM MADE OPTIONS:**