

## KOMBIC 100 DOWNLIGHT

K11RD1540WF930NB



## KOMBIC 100 RD 1500 IP43 9WW WFL BK/BK

## Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in black finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD® available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011


Weight: 382 g

Installation: Recessed

## TECHNICAL SPECIFICATIONS:

Light output:	1.015 lm	°K :	3000
Plum:	13,4W	CRI :	90
Efficacy:	75,7 lm/w	R9 :	62
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	12W		

Light output tolerance +/- 10%



## CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RD1540WF930NBB

KOMBIC 100 RD 1500 IP43 9WW WFL BK/BK

PHOTOMETRIC DATA :

