

KOMBIC 100 DOWNLIGHT

K11RD1540WF935NBW




KOMBIC 100 RD 1500 IP43 935 WFL BK/WH

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3500K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: >100.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD® available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011**Weight:** 382 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.076 lm	°K :	3500
Plum:	9,4W	CRI :	90
Efficacy:	114,5 lm/w	R9 :	61
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	>100.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	8,5W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD1540WF935NBW

KOMBIC 100 RD 1500 IP43 935 WFL BK/WH

PHOTOMETRIC DATA :

