

## KOMBIC 100 DOWNLIGHT

K11RD1540WFWB3NWW

- KOMBIC 100 RD 1200 IP43 WBW WFL WH/WH

**Description:**

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI95. Luminaire with electronic wiring included. Insolation Class II. Lifetime: >100.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Matte white RAL 9010
**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.221 lm	<b>°K :</b>	3000
<b>Plum:</b>	13,5W	<b>CRI :</b>	95
<b>Efficacy:</b>	90,4 lm/w	<b>R9 :</b>	99
<b>UGR:</b>	<19		
<b>LED Lifetime:</b>	>100.000h L90 B10 (Ta=25°C)		
<b>Power:</b>	11,8W		

*Light output tolerance +/- 10%*
**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD1540WFWB3NWW

KOMBIC 100 RD 1200 IP43 WBW WFL WH/WH

PHOTOMETRIC DATA :

