


KOMBIC 100 DOWNLIGHT

K11RD1543EL927DBB


- KOMBIC 100 RD 1500 IP43 9VWW ELI. D B/B

**Description:**

KOMBIC 100 round recessed downlight by LAMP. Reflector made of recycLED polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in black and frame in black finish. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring Dali included. Insulation class II. LED life time: >100.000h L90 B10 (Ta=25°C). With IP43 degree of protection. Group 0 photobiological safety.

Finish: Matte black RAL 9011**Weight:** 517 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.268 lm	°K :	2700
Plum:	14W	CRI :	90
Efficacy:	90,6 lm/w	R9 :	57
Type:	COB	MacAdam:	3
LED Lifetime:	>100.000h L90 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	12,2W	Gear:	Adjustable DALI

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD1543EL927DBB

KOMBIC 100 RD 1500 IP43 9VWW ELI. D B/B

PHOTOMETRIC DATA :

