


KOMBIC 100 DOWNLIGHT

K11RD1543EL927NMW

- KOMBIC 100 RD 1500 IP43 9VWW ELI. MA/W

**Description:**

KOMBIC 100 round recessed downlight by LAMP. Reflector made of recycLED polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and frame in white finish. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring Dali included. Insulation class II. LED life time: 50000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety.

Finish: metalized polycarbonate mate**Weight:** 517 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.239 lm	°K :	2700
Plum:	13,7W	CRI :	90
Efficacy:	90,4 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	13W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD1543EL927NMW

KOMBIC 100 RD 1500 IP43 9VWW ELI. MA/W

PHOTOMETRIC DATA :

