


KOMBIC 100 DOWNLIGHT

K11RD1543EL935NBW



KOMBIC 100 RD 1500 IP43 935 ELI. BK/WH

Description:

KOMBIC 100 round recessed downlight by LAMP. Reflector made of recycLED polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in black and frame in white finish. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsink made of die-cast aluminium. COB LED, colour temperature 3500K with CRI90. Luminaire with electronic wiring included. Insulation class II. LED life time: >100.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety.

Finish: Matte black RAL 9011


Weight: 517 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.362 lm	°K :	3500
Plum:	14W	CRI :	90
Efficacy:	97,3 lm/w	R9 :	61
Type:	COB	MacAdam:	3
LED Lifetime:	>100.000h L90 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	12,2W	Gear:	Electronic

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RD1543EL935NBW

KOMBIC 100 RD 1500 IP43 935 ELI. BK/WH

PHOTOMETRIC DATA :

