

# KOMBIC 100 DOWNLIGHT

K11RD1543WW930NBB




## KOMBIC 100 RD 1500 IP43 9WW WW BK/BK

### Description:

KOMBIC 100 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in black. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insulation class II. LED lifetime: 50000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. WALL WASHER optics to control light distribution towards the vertical surface without dark areas.

**Finish:** Matte black RAL 9011

**Weight:** 517 g




**Installation:** Recessed

### TECHNICAL SPECIFICATIONS:

<b>Light output:</b>	940 lm	<b>°K :</b>	3000
<b>Plum:</b>	13,7W	<b>CRI :</b>	90
<b>Efficacy:</b>	68,6 lm/w	<b>R9 :</b>	60
<b>Type:</b>	COB	<b>MacAdam:</b>	3
<b>LED Lifetime:</b>	50.000 L90 B10 (Ta=25°C)	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Power:</b>	19W	<b>Gear:</b>	Electronic

*Light output tolerance +/- 10%*



### CUSTOM MADE OPTIONS:



# KOMBIC 100 DOWNLIGHT

K11RD1543WW930NBB

KOMBIC 100 RD 1500 IP43 9WW WW BK/BK

**PHOTOMETRIC DATA :**

K11RD1543WW930NBB  
 $\eta = 100\%$   
 $I_{max} = 1366 \text{ cd/klm}$   
 UTE: 1,00B  
 CIE: 79 100 100 100 100

