

KOMBIC 100 DOWNLIGHT

K11RD1543WW940DBB




KOMBIC 100 RD 1500 IP43 9NW WW DA BK/BK

Description:

LAMP Round recessed downlight KOMBIC 100 RD 1500 Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in Wallwasher optic option, suitable for vertical plane lighting or work areas surroundings. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 4000K and CRI90. Electronic DALI gear included. IP43 rated. Insulation Class II. Photobiological safety group 0. LED life time: 50.000 L90 B10. Available finishes: White and black. Environmental Product Declaration - EPD® available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011**Weight:** 517 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.003 lm	°K :	4000
Plum:	13,7W	CRI :	90
Efficacy:	73,2 lm/w	R9 :	50
Type:	COB	MacAdam:	3
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	13W	Gear:	Adjustable DALI

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD1543WW940DBB

KOMBIC 100 RD 1500 IP43 9NW WW DA BK/BK

PHOTOMETRIC DATA :

