

KOMBIC 100 DOWNLIGHT

K11RD1543WW940DWW




KOMBIC 100 RD 1500 IP43 9NW WW DA WH/WH

Description:

LAMP Round recessed downlight KOMBIC 100 RD 1500 Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in Wallwasher optic option, suitable for vertical plane lighting or work areas surroundings. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 4000K and CRI90. Electronic DALI gear included. IP43 rated. Insulation Class II. Photobiological safety group 0. LED life time: 50.000 L90 B10. Available finishes: White and black. Environmental Product Declaration - EPD® available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010**Weight:** 517 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Plum:	13,7W	°K :	4000
Type:	COB	CRI :	90
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	R9 :	50
Power:	13W	MacAdam:	3
		Power Supply:	220-240V 50/60Hz
		Gear:	Adjustable DALI

**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD1543WW940DWW

KOMBIC 100 RD 1500 IP43 9NW WW DA WH/WH

PHOTOMETRIC DATA :

