

# KOMBIC 100 DOWNLIGHT

K11RD1543WW940NWW



## KOMBIC 100 RD 1500 IP43 9NW WW WH/WH

### Description:

KOMBIC 100 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insulation class II. LED lifetime: 50000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. WALL WASHER optics to control light distribution towards the vertical surface without dark areas.


**Finish:** Matte white RAL 9010

**Weight:** 517 g

**Installation:** Recessed

### TECHNICAL SPECIFICATIONS:

<b>Plum:</b>	13,7W	<b>°K :</b>	4000
<b>Type:</b>	COB	<b>CRI :</b>	90
<b>LED Lifetime:</b>	50.000 L90 B10 (Ta=25°C)	<b>R9 :</b>	50
<b>Power:</b>	13W	<b>MacAdam:</b>	3
		<b>Power Supply:</b>	220-240V 50/60Hz
		<b>Gear:</b>	Electronic



### CUSTOM MADE OPTIONS:



# KOMBIC 100 DOWNLIGHT

K11RD1543WW940NWW

KOMBIC 100 RD 1500 IP43 9NW WW WH/WH

**PHOTOMETRIC DATA :**

K11RD1543WW940NWW  
 $\eta = 100\%$   
 $I_{max} = 1058 \text{ cd/klm}$   
 UTE: 1,00C  
 CIE: 70 93 99 100 100

