KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11RD2023RF930DWW — **KOMBIC 100 RD 2000 IP23 9WW RF FL DA W/W**

Description:

Finish: Matte white RAL 9010

Weight: 382 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.893 lm		**ºK :**	3000
Plum:	20,3W		**CRI :**	90
Efficacy:	93,2 lm/w		**MacAdam:**	3
UGR:	<19		**Power Supply:**	220-240V 50/60Hz
Type:	COB		**Gear:**	Adjustable DALI
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)			
Power:	19W			

Light output tolerance +/- 10%

IP
20 INT
23 EXT

EPD

K11RD2023RF930DWW   KOMBIC 100 RD 2000 IP23 9WW RF FL DA W/W

PHOTOMETRIC DATA :

K11RD2023RF930DWW

η = 100%

Imax = 2200 cd/klm

UTE:

CIE: 98 99 100 100 100

180°

90°   90°

0°

alpha = 33,3º

100%
75%   BACK   FRONT
50%   50,0 %   50,0 %
25%
-8H   -4H   0H   4H   8H

Melanopic Lux Ratio: 0.550

3000K 2500K 2000K
4000K   3667K
6000K
10000K

Rf
140
130   1 - Limits on the Planckian locus
120
110
100   Rg
90
80   2 - Limits for practical sources
70   **Rf 90.1 - Rg 100.3**
60
50 60 70 80 90 100

12-03-2025

Data according to regulations 2019/2020/EU and 2019/2015/EU