Product datasheet

KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11RD2023RW940DWW — **KOM 100 RD 2000 IP23 9NW RF WFL DA WH/WH**

Description:

Finish: Shiny white RAL 9010

Weight: 382 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.902 lm	**ºK :**	4000
Plum:	20,3W	**CRI :**	90
Efficacy:	93,7 lm/w	**R9 :**	65
Type:	COB	**MacAdam:**	3
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	**Power Supply:**	220-240V 50/60Hz
Power:	19W	**Gear:**	Adjustable DALI

Light output tolerance +/- 10%

EPD

12-03-2025

K11RD2023RW940DWW   KOM 100 RD 2000 IP23 9NW RF WFL DA WH/WH

PHOTOMETRIC DATA :

K11RD2023RW940DWW

η = 100%

Imax = 1215 cd/klm

UTE: 1,00A

CIE: 94 97 99 100 100

alpha = 59,8º

BACK   FRONT

49,9 %   49,9 %

Melanopic Lux Ratio: 0.768

Rf

Rf 88.8 – Rg 97.4

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

12-03-2025

Pág.   2 / 2

Data according to regulations 2019/2020/EU and 2019/2015/EU