

# KOMBIC 100 DOWNLIGHT


K11RD20400P930DWW



## KOMBIC 100 RD 2000 IP43 9WW OP DA WH/WH

### Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety.



**Finish:** Matte white RAL 9010


**Weight:** 425 g

**Installation:** Recessed

### TECHNICAL SPECIFICATIONS:

<b>Light output:</b>	1.642 lm	<b>°K :</b>	3000
<b>Plum:</b>	19,1W	<b>CRI :</b>	90
<b>Efficacy:</b>	86 lm/w	<b>R9 :</b>	67
<b>Type:</b>	COB	<b>MacAdam:</b>	3
<b>LED Lifetime:</b>	50.000 L70 B10 (Ta=25°C)	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Power:</b>	17W	<b>Gear:</b>	Adjustable DALI

*Light output tolerance +/- 10%*



### CUSTOM MADE OPTIONS:



# KOMBIC 100 DOWNLIGHT

K11RD20400P930DWW

KOMBIC 100 RD 2000 IP43 9WW OP DA WH/WH

**PHOTOMETRIC DATA :**

