


KOMBIC 100 DOWNLIGHT

K11RD20400P930NMW



KOMBIC 100 RD 2000 IP43 9WW OP MA/WH

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.


Finish: metalized polycarbonate mate

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.571 lm	°K :	3000
Plum:	19,1W	CRI :	90
Efficacy:	82,3 lm/w	R9 :	67
Type:	COB	MacAdam:	3
LED Lifetime:	50.000 L70 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	12W	Gear:	Electronic

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RD20400P930NMW

KOMBIC 100 RD 2000 IP43 9WW OP MA/WH

PHOTOMETRIC DATA :

