

KOMBIC 100 DOWNLIGHT

K11RD20400P940DWW



KOMBIC 100 RD 2000 IP43 9NW OP DA WH/WH


Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Installation: Recessed
TECHNICAL SPECIFICATIONS:

Light output:	1.785 lm	°K :	4000
Plum:	19,1W	CRI :	90
Efficacy:	93,5 lm/w	R9 :	65
Type:	COB	MacAdam:	3
LED Lifetime:	50.000 L70 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	17W	Gear:	Adjustable DALI

Light output tolerance +/- 10%
**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD20400P940DWW

KOMBIC 100 RD 2000 IP43 9NW OP DA WH/WH

PHOTOMETRIC DATA :

