

## KOMBIC 100 DOWNLIGHT


K11RD2040OP9TWDWW




## KOMBIC 100 RD 2000 IP43 TW OPAL DA WH/WH

**Description:**

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, with dynamic white colour temperature (2700-6500K) with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 70.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Matte white RAL 9010**Weight:** 550 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.246 lm	<b>°K :</b>	2700-6500
<b>Plum:</b>	20,7W	<b>CRI :</b>	90
<b>Efficacy:</b>	60,2 lm/w	<b>MacAdam:</b>	3
<b>Type:</b>	COB	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	70.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Adjustable DALI
<b>Power:</b>	16W		

**Light output tolerance +/- 10%**

KOMBIC 100 DOWNLIGHT

K11RD20400P9TWDWW

KOMBIC 100 RD 2000 IP43 TW OPAL DA WH/WH

PHOTOMETRIC DATA :

