KOMBIC 100 DOWNLIGHT



K11RD2040WF927DBW

-	KOMBIC 100	RD 2000	IP43	9VWW	WFL	DA	B/W
---	------------	----------------	------	------	-----	----	-----

Description:

Finition: Noir mat RAL 9011

SPÉCIFICATIONS TECHNIQUES:

Flux lumineux: 1.396 lm °K: 2700 Plum: 20,3W IRC: 90 Efficacité: 68,7 lm/w R9: 57

UGR: <19 Type: СОВ

Durée de vie LED: 50.000 L80 B10 (Ta=25°C)

Tolérance de flux lumineux +/- 10%

ΙP



OPTIONS PERSONNALISABLES:





















KOMBIC 100 DOWNLIGHT



K11RD2040WF927DBW

KOMBIC 100 RD 2000 IP43 9VWW WFL DA B/W

DONNÉES PHOTOMÉTRIQUES:

$$\label{eq:continuity} \begin{split} \text{K11RD2040WF927DBW} \\ \eta &= 100\% \\ \text{Imax} &= 1327 \text{ cd/klm} \\ \text{UTE:} \end{split}$$

CIE: 99 100 100 100 100



K11RD2040WF927DBW
η = 100%
Imax = 1327 cd/klm
UTE:
CIE: 99 100 100 100 100











