Product datasheet

KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11RD2040WF930NBW **-** **KOMBIC 100 RD 2000 IP43 9WW WFL BK/WH**

Description:

ø99 | 25 | 75

Finish: Matte black RAL 9011

TECHNICAL SPECIFICATIONS:

Light output:	1.472 lm		**ºK :**	3000
Plum:	20,3W		**CRI :**	90
Efficacy:	72,5 lm/w		**R9 :**	60
UGR:	<19			
Type:	COB			
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)			

Light output tolerance +/- 10%

IP
20 INT
43 EXT

EPD

CUSTOM MADE OPTIONS:

1-10V | | | | ↑lm | LED RETAIL | | PUSH | TRIAC | K

K11RD2040WF930NBW　　　　KOMBIC 100 RD 2000 IP43 9WW WFL BK/WH

PHOTOMETRIC DATA :

K11RD2040WF930NBW

η = 100%

Imax = 1327 cd/klm

UTE:

CIE: 99 100 100 100 100

alpha = 56,2º

BACK　　　FRONT

50,0 %　　　50,0 %

Melanopic Lux Ratio: 0.559

Rf 91.0 - Rg 100.0

Tel.　+34937366800

Web　www.lamp.es

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

12-03-2025

Pág.　2 / 2

Data according to regulations 2019/2020/EU and 2019/2015/EU