# **KOMBIC 100 DOWNLIGHT**




# K11RD2040WF940DBB



# KOMBIC 100 RD 2000 IP43 9NW WFL DA BK/BK

# Description:

Round recessed downlight model KOMBIC 100 RD 2000 IP43 9NW WFL DA BK/BK, LAMP brand. Reflector made of polycarbonate. Interior reflector and frame in black finish, injected die cast aluminium heat sink. Model for LED COB, with neutral white colour temperature and control DALI gear included. IP43 protection rating. Optic Wide Flood to achieve a controlled light distribution and low glare level, less than UGR 17. Insulation class II. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte black RAL 9011

Weight: 442 g

Installation: Recessed

# **TECHNICAL SPECIFICATIONS:**

Light output: 1.552 lm °K: 4000 Plum: 20,3W CRI: 90 Efficacy: 76,4 lm/w R9: 66 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

18W Power:

# Light output tolerance +/- 10%





























# **CUSTOM MADE OPTIONS:**





















# **KOMBIC 100 DOWNLIGHT**



K11RD2040WF940DBB

# KOMBIC 100 RD 2000 IP43 9NW WFL DA BK/BK

# **PHOTOMETRIC DATA:**

K11RD2040WF940DBB  $\eta$  = 100% Imax = 1327 cd/klm UTE:

CIE: 99 100 100 100 100



