

KOMBIC 100 DOWNLIGHT

K11RD2040WF940DWW



KOMBIC 100 RD 2000 IP43 9NW WFL DA WH/WH

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CR90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19.

Finish: Matte white RAL 9010


Weight: 442 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.640 lm	°K :	4000
Plum:	20,3W	CRI :	90
Efficacy:	80,7 lm/w	R9 :	66
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Adjustable DALI
LED Lifetime:	50.000 L80 B10 (Ta=25°C)		
Power:	18W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RD2040WF940DWW

KOMBIC 100 RD 2000 IP43 9NW WFL DA WH/WH

PHOTOMETRIC DATA :

K11RD2040WF940DWW
 $\eta = 100\%$
 $I_{max} = 1265 \text{ cd/klm}$
 UTE: 1,00A
 CIE: 95 99 100 100 100

