

KOMBIC 100 DOWNLIGHT

K11RD2040WF9TWDWW



KOMBIC 100 RD 2000 IP43 TW WFL DA WH/WH

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in black finish. Heatsink made of die-cast aluminium. COB LED, with dynamic white colour temperature (2700-6500K) with CRI90. Luminaire with electronic wiring Dali DT8 included. Insolation Class II. Lifetime: 70.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution.

Finish: Matte white RAL 9010


Weight: 550 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.050 lm	°K :	2700-6500
Plum:	20,7W	CRI :	90
Efficacy:	50,7 lm/w	MacAdam:	3
UGR:	<16	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Adjustable DALI
LED Lifetime:	70.000 L80 B10 (Ta=25°C)		
Power:	16W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RD2040WF9TWDWW

KOMBIC 100 RD 2000 IP43 TW WFL DA WH/WH

PHOTOMETRIC DATA :

