


KOMBIC 100 DOWNLIGHT

K11RD2065OP840NWW




KOMBIC 100 RD 2000 IP65 NW OPAL WH/WH

Description:

Round recessed downlight model KOMBIC 100 RD 2000 IP65 NW OPAL WH/WH, LAMP brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Reflector made of polycarbonate. Matte blanc interior reflector and frame in white finish, and optical film, die cast aluminium heat sink. Model for LED COB, with 4000K colour temperature, CRI80 and control gear included. IP65 protection rating. Insulation class II. Group 0 photobiological safety. Lifetime: 50.000h L80 B10.

Finish: Matte white RAL 9010**Weight:** 517 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.541 lm	°K :	4000
Plum:	13,4W	CRI :	80
Efficacy:	115 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	13W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD2065OP840NWW

KOMBIC 100 RD 2000 IP65 NW OPAL WH/WH

PHOTOMETRIC DATA :

