
KOMBIC 100 DOWNLIGHT

K11RD2065OPWB4NMW



Description:

Round recessed downlight model KOMBIC 100 RD 1800 IP65 WBW OP MA/WH, LAMP brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Reflector made of polycarbonate. Matte metallic interior reflector and frame in white finish, and optical film, die cast aluminium heat sink. Model for LED COB, with 4000K colour temperature, CRI95 and control gear included. IP65 protection rating. Insulation class II. Group 0 photobiological safety. Lifetime: 60.000h L80 B10.



Finish: metalized polycarbonate mate Weight: 517 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Plum:	20W	⁰K :	4000
Туре:	СОВ	CRI :	97
LED Lifetime:	60.000 L80 B10 (Ta=25⁰C)	MacAdam:	3
Power:	17,2W	Power Supply:	220-240V 50/60Hz
		Gear:	Electronic



CUSTOM MADE OPTIONS:



Worktitude for light

KOMBIC 100 DOWNLIGHT

K11RD2065OPWB4NMW

KOMBIC 100 RD 1800 IP65 WBN OP MA/WH



PHOTOMETRIC DATA :

