KOMBIC 100 DOWNLIGHT

K11RD2523RF840DBW

- KOMBIC 100 RD 2500 IP23 NW RF FL DA B/W

Description:

Finish: Matte black RAL 9011 Weight: 442 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	2.185 lm	°К:	4000	
Plum:	20,3W	CRI :	80	
Efficacy:	107,6 lm/w	R9 :	80	
UGR:	<19	MacAdam:	3	
Туре:	СОВ	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI	
Power:	19W			

Light output tolerance +/- 10%



Tel. +34937366800 Web www.lamp.es



KOMBIC 100 DOWNLIGHT

K11RD2523RF840DBW

KOMBIC 100 RD 2500 IP23 NW RF FL DA B/W



PHOTOMETRIC DATA :

K11RD2523RF840DBW	180°	alpha = 33,1°	100%	BACK	FRONT
η = 100%		\wedge	75%		
lmax = 2279 cd/klm		/ \	50%	50,0 %	50,0 %
UTE:	90° 90°		00 /0		\mathcal{M}
CIE: 100 100 100 100 100			25%		
	09			-8H -4H	OH 4H 8H