

## KOMBIC 100 DOWNLIGHT

K11RD2523RF840NBW




## KOMBIC 100 RD 2500 IP23 NW RF FL BK/WH

**Description:**

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Matte black RAL 9011**Weight:** 442 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	2.185 lm	<b>°K :</b>	4000
<b>Plum:</b>	19,8W	<b>CRI :</b>	80
<b>Efficacy:</b>	110,3 lm/w	<b>R9 :</b>	80
<b>UGR:</b>	<19	<b>MacAdam:</b>	3
<b>Type:</b>	COB	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	50.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Electronic
<b>Power:</b>	19W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD2523RF840NBW

KOMBIC 100 RD 2500 IP23 NW RF FL BK/WH

PHOTOMETRIC DATA :

