

KOMBIC 100 DOWNLIGHT

K11RD2523RW840DBW



KOMBIC 100 RD 2500 IP23 NW RF WFL DA B/W

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.


Finish: Matte black RAL 9011

Weight: 442 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	2.002 lm	°K :	4000
Plum:	20,3W	CRI :	80
Efficacy:	98,6 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	19W		

Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RD2523RW840DBW

KOMBIC 100 RD 2500 IP23 NW RF WFL DA B/W

PHOTOMETRIC DATA :

