

KOMBIC 100 DOWNLIGHT

K11RD2540OP830NMW




KOMBIC 100 RD 2500 IP43 WW OPAL MA/WH

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate**Weight:** 392 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.867 lm	°K :	3000
Plum:	19,1W	CRI :	80
Efficacy:	97,8 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	17W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD2540OP830NMW

KOMBIC 100 RD 2500 IP43 WW OPAL MA/WH

PHOTOMETRIC DATA :

