

# KOMBIC 100 DOWNLIGHT

K11RD2543WW830NWW



## KOMBIC 100 RD 2500 IP43 WW WW WH/WH

### Description:

KOMBIC 100 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insulation class II. LED lifetime: 50000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. WALL WASHER optics to control light distribution towards the vertical surface without dark areas.

**Finish:** Matte white RAL 9010


**Weight:** 517 g

**Installation:** Recessed

### TECHNICAL SPECIFICATIONS:

<b>Light output:</b>	2.099 lm	<b>°K :</b>	3000
<b>Plum:</b>	19,8W	<b>CRI :</b>	80
<b>Efficacy:</b>	106 lm/w	<b>MacAdam:</b>	3
<b>Type:</b>	COB	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	50.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Electronic
<b>Power:</b>	19W		

*Light output tolerance +/- 10%*



### CUSTOM MADE OPTIONS:



# KOMBIC 100 DOWNLIGHT

K11RD2543WW830NWW

KOMBIC 100 RD 2500 IP43 WW WW WH/WH

## PHOTOMETRIC DATA :

K11RD2543WW830NWW  
 $\eta = 100\%$   
 $I_{max} = 1058 \text{ cd/klm}$   
UTE: 1,00C  
CIE: 70 93 99 100 100

