

# KOMBIC 100 DOWNLIGHT


K11RD2543WW840DBB



**KOMBIC 100 RD 2500 IP43 NW WW DA BK/BK**

**Description:**

KOMBIC 100 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in black. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring dali included. Insulation class II. LED lifetime: 50000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. WALL WASHER optics to control light distribution towards the vertical surface without dark areas.



**Finish:** Matte black RAL 9011

**Weight:** 517 g

**Installation:** Recessed

**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.632 lm	<b>°K :</b>	4000
<b>Plum:</b>	19,8W	<b>CRI :</b>	80
<b>Efficacy:</b>	82,4 lm/w	<b>MacAdam:</b>	3
<b>Type:</b>	COB	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	50.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Adjustable DALI
<b>Power:</b>	19W		

*Light output tolerance +/- 10%*



**CUSTOM MADE OPTIONS:**



# KOMBIC 100 DOWNLIGHT

K11RD2543WW840DBB

KOMBIC 100 RD 2500 IP43 NW WW DA BK/BK

## PHOTOMETRIC DATA :

