

KOMBIC 100 DOWNLIGHT

K11RD2543WW840DWW



KOMBIC 100 RD 2500 IP43 NW WW DA WH/WH

Description:

KOMBIC 100 round recessed downlight by LAMP. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring dali included. Insulation class II. LED lifetime: 50000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. WALL WASHER optics to control light distribution towards the vertical surface without dark areas.

Finish: Matte white RAL 9010

Weight: 517 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	2.203 lm	°K :	4000
Plum:	19,8W	CRI :	80
Efficacy:	111,3 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	19W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RD2543WW840DWW

KOMBIC 100 RD 2500 IP43 NW WW DA WH/WH

PHOTOMETRIC DATA :

K11RD2543WW840DWW
 $\eta = 100\%$
 $I_{max} = 1058 \text{ cd/klm}$
UTE: 1,00C
CIE: 70 93 99 100 100

