


## KOMBIC 100 DOWNLIGHT

K11RD2555OP830DMW




## KOMBIC 100 RD 2500 IP55 WW OPAL DA MA/WH

**Description:**

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP55 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** metalized polycarbonate mate**Weight:** 517 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.867 lm	<b>°K :</b>	3000
<b>Plum:</b>	19,1W	<b>CRI :</b>	80
<b>Efficacy:</b>	97,7 lm/w	<b>MacAdam:</b>	3
<b>Type:</b>	COB PHILIPS	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	50.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Adjustable DALI
<b>Power:</b>	17W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD2555OP830DMW

KOMBIC 100 RD 2500 IP55 WW OPAL DA MA/WH

PHOTOMETRIC DATA :

