


KOMBIC 100 DOWNLIGHT

K11RD2555OP840DMW




KOMBIC 100 RD 2500 IP55 NW OPAL DA MA/WH

Description:

Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP55 degree of protection. Group 0 photobiological safety.

Finish: metalized polycarbonate mate**Weight:** 517 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.978 lm	°K :	4000
Plum:	19,1W	CRI :	80
Efficacy:	103,6 lm/w	MacAdam:	3
Type:	COB PHILIPS	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	17W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 DOWNLIGHT

K11RD2555OP840DMW

KOMBIC 100 RD 2500 IP55 NW OPAL DA MA/WH

PHOTOMETRIC DATA :

