

KOMBIC 100 DOWNLIGHT

K11RO2040WF940NWW




KOMBIC 100 RO 2000 IP43 WFL 9NW W/W

Description:

Adjustable recessed downlight model KOMBIC 100 RO 2000 from the LAMP brand. Aluminum injection frame and R-PC FR WHITE TM recycled polycarbonate reflector with bromine-free flame retardant. Flammability degree V0 according to UL94. Interior reflector finished in white. Adjustable luminaire +/-20° with wide flood optics for greater efficiency and control of light distribution and reduction of UGR<19 glare. Aluminum injection heat sink with cataphoresis treatment for greater thermal stability. COB LED, with 4000K color temperature with CRI90. Electronic equipment ON OFF included. With an IP43 degree of protection. Insulation class II. Photobiological safety group 0. Hours of life: >100.000 L90 B10. Finished in black and white.

Finish: Matte white RAL 9010

Weight: 510 g




Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.519 lm	°K :	4000
Plum:	14W	CRI :	90
Efficacy:	108,5 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Electronic
LED Lifetime:	>100.000 L90 B10 (Ta=25°C)		
Power:	12W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11RO2040WF940NWW

KOMBIC 100 RO 2000 IP43 WFL 9NW W/W

PHOTOMETRIC DATA :

