KOMBIC 100 SURFACE



K11SF1523RF927NMW

KOMBIC 100 SF 1500 IP23 9VWW RF FL MA/WH

Description:

Finish: metalized polycarbonate mate

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.325 lm °K: 2700 Plum: 14,1W CRI: 90 Efficacy: 93,9 lm/w R9: 58 UGR: <19 3

MacAdam: Type: СОВ

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power Supply:

220-240V 50/60Hz

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE




K11SF1523RF927NMW


KOMBIC 100 SF 1500 IP23 9VWW RF FL MA/WH


PHOTOMETRIC DATA:


K11SF1523RF927NMW $\eta = 100\%$ Imax = 2200 cd/klm UTE:


CIE: 98 99 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH