

K11SF1523RF930DMW

- KOMBIC 100 SF 1500 IP23 9WW RF FL DA M/W



Description:**Finish:** metalized polycarbonate mate**Weight:** 712 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

| | | | |
|----------------------|--------------------------|----------------------|------------------|
| Light output: | 1.382 lm | °K : | 3000 |
| Plum: | 13,9W | CRI : | 90 |
| Efficacy: | 99,4 lm/w | MacAdam: | 3 |
| UGR: | <19 | Power Supply: | 220-240V 50/60Hz |
| Type: | COB | Gear: | Adjustable DALI |
| LED Lifetime: | 50.000 L80 B10 (Ta=25°C) | | |
| Power: | 13W | | |

Light output tolerance +/- 10%

K11SF1523RF930DMW **KOMBIC 100 SF 1500 IP23 9WW RF FL DA M/W**

PHOTOMETRIC DATA :



KOMBIC 100 SURFACE

ACCESORIES :

Suspension



Product code:
K11SUADLATBK

Description:
KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:
K11SUADLATWH

Description:
KOMBIC 100 SF ADAPT. LATERAL CABLE WH