KOMBIC 100 SURFACE



K11SF1523RF930DWB

- KOMBIC 100 SF 1500 IP23 9WW RF FL DA W/B

Description:

Finish: Matte white RAL 9010

Weight: 712 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 1.382 lm
 ⁰K :
 3000

 Plum:
 13,9W
 CRI :
 90

 Efficacy:
 99,4 lm/w
 MacAdam:
 3

 UGR:
 <19</th>
 Power Supply:
 220-240V 50/60Hz

 Type:
 COB
 Gear:
 Adjustable DALI

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

Power: 13W

Light output tolerance +/- 10%

EPD

Tel. +34937366800 Web www.lamp.es

KOMBIC 100 SURFACE




K11SF1523RF930DWB


KOMBIC 100 SF 1500 IP23 9WW RF FL DA W/B


PHOTOMETRIC DATA:


K11SF1523RF930DWB $\eta = 100\%$ Imax = 2200 cd/klm UTE:


CIE: 98 99 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH