# **KOMBIC 100 SURFACE**



K11SF1523RF940DMB

- KOMBIC 100 SF 1500 IP23 9NW RF FL DA M/B

Description:

Finish: metalized polycarbonate mate

Weight: 712 g

Installation: Recessed

# **TECHNICAL SPECIFICATIONS:**

Light output: 1.474 lm °K: 4000 Plum: 13,9W CRI: 90 Efficacy: 106 lm/w R9: 65 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 13W

Light output tolerance +/- 10%

EPD

# **KOMBIC 100 SURFACE**



K11SF1523RF940DMB


# KOMBIC 100 SF 1500 IP23 9NW RF FL DA M/B


### **PHOTOMETRIC DATA:**


 $\label{eq:K11SF1523RF940DMB} $\eta = 100\%$$ $|\text{Imax} = 2200 \text{ cd/klm}$$ $|\text{UTE:}$$ 


CIE: 98 99 100 100 100




















# **KOMBIC 100 SURFACE**



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

**Product code:**K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH